



Refer to colour chart for vinyl selection

QUANTITY	PAD THICKNESS	LOCATION

GENERAL NOTES / CONFIRMATIONS:

1. WORK PROVIDED BY OTHERS:
 - 1.1. BACKING AND BLOCKING TO WALLS AS REQUIRED
2. ARCHITECT AND/OR GENERAL CONTRACTOR SHALL COORDINATE LOCATIONS OF PADDING WITH ANY EQUIPMENT POTENTIALLY SUBJECT TO INTERFERENCE
3. LOCATIONS OF CUT OUTS FOR ELECTRICAL OUTLETS, SWITCHES, VENTS OR OTHER OBSTRUCTIONS TO BE SITE VERIFIED. GENERAL CONTRACTOR IS RESPONSIBLE FOR VERIFYING THAT ALL ITEMS REQUIRING CUT OUT(S) ARE INSTALLED PRIOR TO SITE MEASUREMENTS
4. VINYL IS 18OZ FR RATED TO NFPA701 USA/CPAI 84 SECTION (2 SECOND EXTINGUISH) AND CAN/ULCS 109, MILDEW ROT AND UV RESISTANT
5. FOAM IS OPEN CELL POLYURETHANE, 2.2 LBS/CUBIC FT., MEETS TB117 FOR SMOLDER FALMMABILITY

Forum Athletic Products
 9 Browning Court Unit 1
 Bolton, ON, Canada L7E 1G8

Phone 905-405-1222
Fax 905-405-8532
Email info@forumathletic.ca
Website www.forumathletic.ca

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY PROPERTY OF FORUM ATHLETIC PRODUCTS INC. THEY MAY NOT BE REPRODUCED OR DISTRIBUTED WITHOUT PRIOR WRITTEN CONSENT FROM FORUM ATHLETIC PRODUCTS INC.

PROJECT:

DESCRIPTION:
F80100 Removable Wall Padding

DWG NO. / PART. NO.
Wall Padding_F80100

REV
A

REV.	DESCRIPTION	DATE