



June 2013

INLAND PLASTICS LTD.

MANUFACTURER AND DISTRIBUTOR

PRODUCT SPECIFICATION SHEET

MS911 Mesh FR

Product Code: MS911_FR61100

BASE FABRIC

Weight Of Base Fabric: 11 oz p.s.y.
Fiber of Base Fabric: Woven Polyester Scrim
Denier of Fabric: 1000 Denier Polyester
Fabric Count: 11 Warp / 11 Weft

TEST METHOD

ASTM D3776

COATED FABRIC

Type of Coating: PVC (Polyvinyl Chloride)
Tapes: Coated prior to weaving
Colors in Stock: Black, Blue, Green, White, Red
Width of Fabric: 61"
Sealing properties: Dielectric & Thermal

MECHANICAL PROPERTIES

| | | |
|------------------------|--|-------------------------|
| Tensile (Grab): | Warp 223 lbs / inch Weft 227 lbs / inch | ASTM D-58034-09 |
| Tongue Tear: | 51 lbs war[| ASTM D751 |
| Low Cold Crack: | No cracking after 24 hours at -40°C 2" mandrel | |
| Mullen Burst: | 50 lbs weft | ASTM D3786 |
| Fire Retardent: | Small & large Flame test Small & large Flame test | CAN/ULC-S109 NFPA701 |

MILDEW AND ROT RESISTANT
ULTRAVIOLET LIGHT RESISTANT

We believe this information is the best currently available on the subject. We make no guarantee of results and assume no obligation or liability in connection with this information.

Branch:
1310 E. Birch Street
Kankakee, IL
60901
Ph: (815) 933-3500
Fax: (815) 933-4500

Branch:
Unit 2, 27533-50th Ave
Langley, BC
V4W 0A2
Ph: (604) 856-8277
Fax: (604) 856-8272

Branch:
842 - 56 St E
Saskatoon, SK
S7K 5Y8
Ph: (306) 931-1122
Fax: (306)934-7078

Branch:
1645 Enterprise Rd
Mississauga, ON
L4W 4L4
Ph: (905) 670-3000
Fax: (905) 670-3003

Head Office
PO Box 2199
Drumheller, AB
T0J 0Y0
Ph: (403) 823 6252
Fax: (403) 823-7310